BUYING AID

FLOORS

GOOD TO KNOW

Laminated flooring can be laid on existing floors, with the exception of thick fixed carpet. Always use the NIVÅ floor lining when laying laminated flooring (sold separately). When laying laminated flooring on concrete or stone, use SPÄRRA plastic foil (sold separately). MARKYTA wall/floor tiles can be laid over existing tiles. The tiles must always be glued.



GUARANTEE

See the guarantee brochure for the conditions.



10 year guarantee for free

You receive a 10-year guarantee on TUNDRA & PRÄRIE laminate floors.

GRATIS 15 jaar garantie 15 year guarantee for free

You receive a 15-year guarantee on GOLV, GRÄSMARK, MYRMARK, ÄNGSMARK laminated flooring and MARKYTA floor and wall tiles.

Don't forget the floor

The floor is such an obvious part of the interior that you would almost forget that it is the foundation for the entire house. A new floor is a beautiful base for your furniture and can turn a sober room into a harmonious place. IKEA sells low-maintenance floors for all tastes and budgets, and for every room, even wet rooms, on the floor or on the wall. They are all easy to lay and make your home feel like new.

Very easy

To lay a floor should be easy. That's why all our laminated floors have a simple click system. Detailed instructions are included and almost all the necessary accessories and tools are also available from IKEA.



CONTENT

CHOOSE THE RIGHT FLOORING	3
LAMINATE	6
ALL PARTS AND PRICES	
SKIRTING BOARD	7
FLOOR LINING	8
HOW MUCH DO YOU NEED?	9
HOW TO LAY THE FLOOR	10
LAMINATE MAINTENANCE	11
WALL/FLOOR TILES	
ALL PARTS AND PRICES	12
HOW MUCH DO YOU NEED?	13
HOW TO LAY THE FLOOR	13
WALL/FLOOR TILE MAINTENANCE	14
SERVICES	16

CHOOSE THE RIGHT FLOORING

A new floor is a beautiful base for your furniture and can turn a sober room into a harmonious one. IKEA sells a large collection of laminate floors that fit with any type of interior. At IKEA you will find a suitable floor for every taste and budget. As of April 2018 our collection of laminate floors is totally renewed to even better fit our customers' wishes. More different types of floors; wide planks, narrow planks, herringbone pattern, you name it, and for every room, even wet rooms, on the floor or on the wall. All our laminate floors have a simple click system, which makes them easy to lay for everybody.

Next to our laminate floors we also started a new product: MARKYTA floor and wall tiles. These tiles can be applied in every type of room. Of course you can lay them on the floors of all the rooms in your home, but you can also use them to cover the walls, which makes them suitable for the bathroom or the kitchen. These tiles are fixed using glue. Our tiles provide a multifunctional solution for all the rooms in your home.





CHOOSE THE RIGHT FLOORING

In order to simplify things for customers, there is an official flooring classification system. The floors are classified according to how much wear the surface will tolerate. Wear is often greater in the hall and kitchen than in the bedroom.

This is the reason why IKEA offers floors of different qualities. If you know where your floor is going, we can help you make the right choice by using the flooring classification below.

	This is the classification for a floor in a frequently used domestic environment, e.g. the living room, and for a floor with light wear in an office environment. Not for damp cellars, wet rooms or rooms with a floor drain.	This is the classification for a floor in a frequently used domestic environment, e.g. the living room, and for a floor with light wear in an office environment. Not for damp cellars, wet rooms or rooms with a floor drain.	This is the classification for a floor in a frequently used domestic environment, e.g. the living room, and for a floor with light wear in an office environment. Not for damp cellars, wet rooms or rooms with a floor drain.	This is the classification for a floor within a heavily used domestic environment, e.g. the hall, kitchen and living room. Also suitable for a floor with normal wear in office and retail environments. Not for damp cellars, wet rooms or rooms with a floor drain.
Room/location:	SLÄTTEN	TUNDRA	PRÄRIE	GOLV
Living room	•	•	•	•
Bedroom	•	•		•
Children's room	•	•	•	•
Kitchen				
Dining room	•	•	•	•
Hallway/entrance	•			•
Storage room	•			•
Utility room				
Bathroom				
Small business/public office	•			
Home office/study	•			
AC-level *	3	3	3	4
Click locking system	Easy Connect	IKEA Lock system **	IKEA Lock system **	IKEA Lock system **
Thickness	6 mm	7 mm	7 mm	8 mm
Plank width	19.4 cm	19.4 cm	19.4 cm	19.4 cm
Guarantee		10 years	10 years	15 years
4 side V groove				•
Light embossed surface				
Heavily embossed surface				•

^{*} The common term used to denote the durability level of laminate flooring is its "AC" rating.

AC ratings are an abbreviated representation of a laminate's resistance to abrasion, impact, stains and cigarette burns.

stst The IKEA Lock system is 50% faster to install than regular locking systems.









This is the classification for a floor within a heavily used domestic environment, e.g. the hall, kitchen and living room. Also suitable for a floor with normal wear in office and retail environments. Not for damp cellars, wet rooms or rooms with a floor drain.

This is the classification for a floor within a heavily used domestic environment, e.g. the hall, kitchen and living room. Also suitable for a floor with normal wear in office and retail environments. Not for damp cellars, wet rooms or rooms with a floor drain.

This is the classification for a floor within a heavily used domestic environment, e.g. the hall, kitchen and living room. Also suitable for a floor with normal wear in office and retail environments. Not for damp cellars, wet rooms or rooms with a floor drain.

This is the classification for a floor within a heavily used domestic environment, e.g. the hall, kitchen and living room. Also suitable for a floor with normal wear in office and retail environments. Not for damp cellars, wet rooms or rooms with a floor drain.

Room/location:	GRÄSMARK	MYRMARK	ÄNGSMARK	MARKYTA
Living room	•	•	•	•
Bedroom	•	•	•	•
Children's room	•	•	•	•
Kitchen				•
Dining room	•	•		•
Hallway/entrance	•	•	•	•
Storage room	•	•		•
Utility room				•
Bathroom				•
Small business/public office				•
Home office/study	•	•	•	•
AC-level *	4	4	4	4
Click locking system	IKEA Lock system **	IKEA Lock system **	IKEA Lock system **	Glue
Thickness	8 mm	8 mm	8 mm	3.2 mm
Plank width	16 cm	24.3 cm	24.3 cm	31 cm
Guarantee	15 years	15 years	15 years	15 years
4 side V groove	•	•		-
Light embossed surface				•
Heavily embossed surface	•	•		

^{*} The common term used to denote the durability level of laminate flooring is its "AC" rating.

AC ratings are an abbreviated representation of a laminate's resistance to abrasion, impact, stains and cigarette burns.


^{**} The IKEA Lock system is 50% faster to install than regular locking systems.


LAMINATE

The primary objective of our various types of laminate floors is that they are easy to lay and that they appear natural. That is why most of our laminate floors have a V-groove, which emphasises the effect of separate planks. TUNDRA and SLATTEN do not have this feature. We also tried to maintain a natural structure, emphasizing visible knots and the grain of the wood.


All our laminate floors have our simple IKEA Lock system, which makes them easy to lay. The planks are easily connected to each other and are instantly locked. The SLÄTTEN has an easy connect system. This system also locks the planks, but laying the floor is more time consuming. With the suitable floor lining you can also lay our laminate floors in rooms with underfloor heating.


IKEA Lock-system





Easy Connect-click system





ALL PARTS AND PRICES

LAMINATE FLOORS



SLÄTTEN laminate floor, 3 m2/pack.
Size 1 plank: 19.4×129 cm. Thickness 6 mm.

Maple effect 904.175.27 **3.99/m²**



GRÄSMARK laminate floor, 2.01 m2/pack. With V groove. Size 1 plank: 16×128.6 cm. Thickness 8 mm.

Oak effect/dark gray antique effect 904.175.70 14.95/m²

Oak effect/light gray antique effect 004.164.76 14.95/m²



 TUNDRA laminate floor, 2.25 m2/pack.

 Size 1 plank: 19.4×128.6 cm. Thickness 7 mm.

 Oak effect
 904.175.32
 5.99/m²

 Oak/Antique effect
 104.175.31
 5.99/m²

 Whitewash/maple effect
 304.175.30
 5.99/m²



 MYRMARK laminate floor, 2.12 m2/pack. With V groove.

 Size 1 plank: 24.3×128.6 cm. Thickness 8 mm.

 Oak effect gray/brown
 904.180.65
 17.95/m²

 White glazed oak effect
 304.164.65
 17.95/m²



Size 1 plank: 19.4×128.6 cm. Thickness 7 mm. 904.175.46 **8.99/m²** Oak effect gray/brown Oak effect/white 604.175.43 8.99/m² 704.175.47 8.99/m² Oak/Antique effect Oak effect/gray 104.175.45 8.99/m² Oak effect 004.190.69 8.99/m² Oak effect/whitewash 204.190.68 8.99/m²

PRÄRIE laminate floor, 2.25 m2/pack. With V groove.



ÄNGSMARK laminate floor, 2.12 m2/pack. With herringbone pattern. Size 1 plank: 24.3×128.6 cm.

Thickness 8 mm.

Gray heterogeneous/oak effect 404.181.95 whitewash oak effect 804.164.77 17.95/m² 17.95/m²



 GOLV laminate floor, 2 m2/pack. With V groove.

 Size 1 plank: 19.4×128.6 cm. Thickness 8 mm.

 Light Oak effect
 304.175.68
 12.95/m²

 Oak effect
 104.175.69
 12.95/m²

ALL PARTS AND PRICES

EDGE MOLDING



SLÄTTEN edge molding, 200 cm.

Maple effect	704.175.28	2.99



TUNDRA edge molding, 200 cm.

Oak effect	604.190.71	2.99
Oak/Antique effect	504.175.34	2.99
Whitewash/maple effect	704.175.33	2.99



PRÄRIE edge molding, 200 cm.

Oak effect gray/brown	504.175.48	2.99
Oak effect/white	104.175.50	2.99
Oak/Antique effect	304.175.49	2.99
Oak effect/gray	604.175.62	2.99
Oak effect	404.190.72	2.99
Oak effect/whitewash	404.175.63	2.99

SKIRTING BOARD



SLÄTTEN skirting board, 200 cm.

Use glue to apply to the wall, available from the DIY store.

Maple effect	504.175.29	4.99
Maple effect	304.173.23	7.55



TUNDRA skirting board, 200 cm. Height 5.8 cm. Use glue to apply to the wall, available from the DIY store.

Oak effect	604.190.71	4.99
Oak/Antique effect	504.175.34	4.99
Whitewash/maple effect	704.175.33	4.99



PRÄRIE skirting board, 200 cm. Height 5.8 cm. Use glue to apply to the wall, available from the DIY store.

Oak effect gray/brown	904.175.65	4.99
Oak effect/white	504.175.67	4.99
Oak/Antique effect	704.175.66	4.99
Oak effect/gray	204.175.64	4.99
Oak effect	204.190.73	4.99
Oak effect/whitewash	004.190.74	4.99



LAVHED skirting board, 200 cm. White.

Use glue to apply to the wall, available from the DIY store.

Height 6 cm	404.182.23	3.50
Height 8 cm	203.905.88	3.99
Height 12 cm	204.182.24	4.99



VIDESNÅR skirting board, 200 cm. White.
Use glue to apply to the wall, available from the DIY

Height 6 cm	904.182.25	3.50
Height 8 cm	004.164.81	3.99
Height 12 cm	704.182.26	4.99



With the TORV accessories you can finish difficult corners and pipes.



TORV inner corner FOR skirting board.

White	502.859.96	1.99



TORV outer corner FOR skirting board.

White	102.860.02	1.99



TORV end cap for skirting board, 2 pcs.



TORV pipe coller, 2 pcs.

For radiator pipes with a diameter of 15, 19 and 22 mm.

White	002.860.07	2.99



FIXA spacers.

store.

To be used on all types laminate flooring. When laying the floor use a spacer every $50\ \mathrm{cm}.$

30 pcs.	302.876.7	5 3.99



TORV end profile, aluminum color. To be used at the end of the floor, for example at the top of the stairs.

95 cm	602.934.58	3.99
200 cm	002.934.61	7.99



TORV connection profile, aluminum color. To be used between two parts of the floor, for example under a door.

95 cm	102.934.65	3.99
200 cm	702.934.67	7.99



TORV equaliser profile, aluminum color. To be used between two parts of the floor of different heights.

95 cm	802.934.62	3.99
200 cm	602.934.63	8.99

FLOOR LINING

Floor lining makes sure that small irregularities are covered and it levels the floor. In addition, the floor lining insulates and dampens noise. When choosing your floor lining you have to ask yourself how important these features are in your case.

The thickness of the floor lining determines the amount of insulation and noise damping. NIVÅ floor lining with a thickness of 2 mm reduces noise by 20 dB, whereas NIVÅ floor lining with a thickness of 5 mm reduces noise by 22 dB. In rooms with underfloor heating we recommend 2 mm floor lining. SPARRA foil is important as a floor lining for concrete floors, which may contain moisture and may cause the floor to expand.

	Existing floor:	You can keep the old flooring	You need to remove the old flooring	Make sure the floor is clean, dry and level	Use SPÄRRA plastic foil moisture barrier	NIVÅ floor lining 2 mm	NIVÅ floor lining 5 mm
Linole	um						
PVC							
Parqu	et						
Cork							
Wood							
Stone	*						
Tiles							
Wall-t	co-wall carpet						
Concr	ete *						
Floor	with underfloor heating	**					

^{*} SPÄRRA plastic foil should also be used in places where there is a possibility of moisture rising through the flooring.

ALL PARTS AND PRICES



SPÄRRA plastic foil, $2 \times 15 \text{ m. } 30 \text{ m2/rol.For}$ concrete or stone floors.

702.947.92 **0.90/m²**



NIVÅ floor lining 2 mm. 1.2×12.5 m. 15 m2/pack. For concrete, stone and/or even floors. Complies with the EPLF® requirements for use in apartment buildings (20 dB noise reduction). Suitable for use with underfloor heating. 2 mm polystyrene. Heat insulation >=0.07m² K/W

302.216.03 **1.99/m²**



NIVÅ floor lining 5 mm. 79×59 cm. 13 pcs. 6.06 m2/pack. For wooden and/or uneven floors. Complies with EPLF ® requirements for use in apartment buildings (20 dB noise reduction). 5 mm polystyrene. Heat insulation >= 0.18 m²K/W

803.215.87 **2.99/m**²

^{**} Floors with electric heating coils must be thermostatically controlled so as not to get too hot (max 27°C). We recommend professional installation.


HOW MUCH DO YOU NEED?


The table below helps you to calculate your flooring requirements per square metre room. The values in the table take into account 10% loss for cutting. However, it is recommended that you add one extra pack per room to allow for errors. Any unopened packs can be returned to IKEA.


Floor area in square metres			6 m ²	9 m²	12 m²	15 m²	18 m²	20 m²	25 m²	30 m²	35 m²	40 m²	
	m²/pack	price/m²											
Floor lining													
SPÄRRA plastic foil for stone and concrete.	30 m²/rol	0.90	Number of rolls	1	1	1	1	1	1	1	2*	2	2
NIVÅ 2 mm floor lining for concrete and even floors.	15 m²/pack	1.99	Number of packs	1	1	1	1	2	2	2	2	3	3
NIVÅ 5 mm floor lining for wooden and uneven floors.	6.06 m²/pack	2.99	Number of packs	1	2	2	3	3	4	5	5	6	7
Laminate floors													
SLÄTTEN	3 m²	3.99	Number of packs	3	4	5	6	7	8	10	11	13	15
TUNDRA	2.25 m²	5.99	Number of packs	3	5	6	8	9	10	13	15	18	20
PRÄRIE	2.25 m ²	8.99	Number of packs	3	5	6	8	9	10	13	15	18	20
GOLV	2.00 m ²	12.95	Number of packs	4	5	7	9	10	11	14	17	20	22
GRÄSMARK	2.01 m ²	14.95	Number of packs	4	5	7	9	10	11	14	17	20	22
MYRMARK	2.12 m ²	17.95	Number of packs	4	5	7	8	10	11	13	16	19	21
ÄNGSMARK	2.12 m²	17.95	Number of packs	4	5	7	8	10	11	13	16	19	21

^{*}Take into account 20 cm overlap.

HOW TO LAY A LAMINATE FLOOR







Key considerations and preparation

- 1. Ensure you have the correct amount of flooring more than what you need. (you can always return full packs).
- 2. Leave the flooring in the room you intend to lay it in for at least 48 hours in its packaging- this allows it to climatise.
- 3. Familiarise yourself with the instructions on the packet ensuring you have all the correct tools.
- 4. First, make sure there is enough space for your underlay material and new floor under any doors.
- Make sure that the existing floor is clean, dry and level. If your existing floor is made of concrete or stone, you should always cover it with SPÄRRA plastic sheeting. All floors also need NIVÅ floor lining in place.
- 6. For the best results lay the boards in the direction of the incoming light.
- Flooring expands and contracts with temperature changes, so ensure you use the FIXA spacers around the perimeter of your flooring.
- 8. The maximum width that you can lay in one piece is 8 meters wide and 12 meters in length. If you want to lay larger areas, use a FIXA connection strip, for example under a door.
- Finally, for a neat finish you can create a nice looking transition between the floor and walls by adding skirting boards and/or edge molding.

FLOOR MAINTENANCE

Laminated flooring should never be sanded, waxed or polished. The hard wearing surface is easy to clean and maintain. Normal cleaning, such as sweeping, vacuuming and dry mopping if the floor is slightly dirty. Stains should be removed with a moist cloth. If needed, the floor should be damp mopped with a mild detergent and dried with a cloth. Soap, wax or floor polish should never be used on laminated flooring, because they leave a film that attracts dirt and dust.

If the floor becomes damaged, you can replace one or several planks. Because laminated flooring doesn't bleach from sunlight, you can replace an old plank with a new one without worrying about any differences in colour.

Tip!

Take good care of your floor by using FIXA felt floor protectors under your furniture and KOLON floor protectors under things with rolling castors. It's also a good idea to put a doormat in front of the entrance as an effective way to stop gravel and pebbles from coming in. Because laminated flooring is wood-based, it's important to always wipe up any water from the floor. NOTE: Never pour water directly on the floor.

WALL/FLOOR TILES


MARKYTA wall and floor tiles are made from polypropylene and can be used in every type of room and on every type of floor or wall. They can be used for a back wall in the kitchen or in wet spaces like the bathroom!

Whether you like a stone pattern, a concrete look or one of our graphical patterns, the choice is yours!

Our tiles are easy to lay. Just apply a layer of MARKYTA glue to the floor or the wall and join the tiles by means of the seal-joint system.

The size of the tiles can easily be made to fit by using a cutter or a saw.

Seal-joint system



ALL PARTS AND PRICES



MARKYTA floor and wall tiles, 1.97 m2/pack. Size of 1 tile: 31.5×62.5 cm. Thickness 3.2 mm.

Beige stone pattern	604.164.78	29.95/m ²
Grey stone pattern	104.182.29	29.95/m ²



MARKYTA floor and wall tiles, 1.97 m2/pack.

Size of 1 tile: 31.5×62.5 cm. Thickness 3.2 mm.

Diamond pattern

Cirkel pattern black/white

light grey/ dark grey 704.182.45 **29.95/m²**

004.182.44 **29.95/m²**



MARKYTA floor and wall tiles, 1.97 m2/pack. Size of 1 tile: 31.5×62.5 cm. Thickness 3.2 mm.

Dark grey concrete pattern	904.182.30	29.95/m ²
Light grey concrete pattern	704.182.31	29.95/m ²



MARKYTA floor and wall tiles, 1.97 m2/pack. Size of 1 tile: 31.5×62.5 cm. Thickness 3.2 mm.

MARKYTA floor and wall tiles 1.97 m2/pack. Size of 1 tile: 31.5×62.5 cm. Thickness 3.2 mm.

Dark grey stone pattern 504.210.79 **29.95/m²** White spectrum stone pattern 104.210.81 29.95/m²



MARKYTA floor and wall tiles, 1.97 m2/pack. Size of 1 tile: 31.5×62.5 cm. Thickness 3.2 mm. Small flower pattern light blue 502.182.32 29.95/m²



MARKYTA floor and wall tiles, 1.97 m2/pack. Size of 1 tile: 31.5×62.5 cm. Thickness 3.2 mm.

Ornament pattern

504.182.46 **29.95/m²** grey/orange



MARKYTA glue. Including glue comb. For 10-12 m2.


5.5 kg 704.266.79 49.95

HOW MUCH DO YOU NEED?

The table below helps you to calculate how many packs of tiles and glue you need. The values in the table take into account 10% loss for cutting. Any unopened packs can be returned to IKEA.

Floor area in squa	are metres			6 m ²	9 m²	12 m²	15 m²	18 m²	20 m²	25 m²	30 m²	35 m²	40 m²
	m²/pack	price/m²											
Wall and floor t	Wall and floor tiles												
MARKYTA	1.97 m²	29.95	Number of packs	4	5	7	9	10	11	14	17	20	23
Glue													
MARKYTA glue	10 m²		Number of buckets	1	1	2	2	2	2	3	3	4	4

HOW TO LAY A TILE FLOOR



You can lay no more than 12 meters in width and/or length in one piece.




Suitable for rooms with underfloor heating, max 27°C.



Markyta can be used over existing tiles. The surface must be flat.



Not suitable for rooms with electric underfloor heating.



Easy to adjust the size. Just cut 2-3 times with a sharp knife and break the tile.

Holes for taps and pipes can be made using a hole saw.



When using the tiles as a back wall in the kitchen, it is sufficient to apply te glue in streaks.



Use our MARKYTA glue for applying the floor/wall tiles.

MAINTENANCE OF FLOOR AND WALL TILES



The hard wearing surface is easy to clean and maintain. Normal cleaning, such as sweeping, vacuuming and dry mopping if the floor is slightly dirty. Stains should be removed with a moist cloth. If needed, the floor should be damp mopped with a mild detergent and dried with a cloth. Laminated flooring should never be sanded, waxed or polished. Never use abrasive products or products with chlorine or bleach.

Tip!

Protect your floor by using FIXA felt floor protectors under your furniture and KOLON floor protectors under furniture with rolling castors. It's also a good idea to put a doormat in front of the entrance as an effective way to stop gravel and pebbles from coming in.

Need extra hands?We have more than enough

Do you want to do everything yourself? Or do you prefer someone else doing it for you? We can help you with whatever you want. Just choose one of our services. For all our services and prices, see IKEA.com/services



Picking and delivery service

If you choose our picking and delivery service, we do all the heavy work for you. We collect all the furniture from your shopping list and we deliver everything to your home.



Transport service

Most of our products are flat packed and designed to easily fit in your car. However, if you prefer, we can deliver everything to your home.



Order & pick up service

Place your order online and collect everything at the shop 4 hours later.